



COUNTRY COLOUR

Variety of colours and unsurpassed durability – for all weather conditions!

2101 White Opaque	2203 Light Ochre Opaque	2204 Ivory Opaque	2205 Sunflower Yellow Opaque	2308 Nordic Red Opaque
2310 Cedar/Red-wood Opaque	2311 Signal Red Opaque	2404 Fir Green Opaque	2501 Labrador Blue Opaque	2506 Royal Blue Opaque
2507 Dove Blue Opaque	2606 Medium Brown Opaque	2607 Dark Brown Opaque	2703 Charcoal Opaque	2704 Dusk Grey Opaque
2708 Pebble Grey Opaque	2716 Anthracite Grey Opaque	2735 Light Grey Opaque	2742 Traffic Grey A Opaque	



Product description:

Opaque, at first slightly satin-gloss then satin, natural oil based finish for wood in outdoor areas. Wood tone and grain is covered. The wood texture remains noticeable. Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weatherproof and UV stable surface does not crack, peel, flake or blister. No sanding necessary, just simply recoat; no primer is needed. Easy and seamless application. Finish stays workable while coating. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3)

Recommended use:

Osmo Country Colour is best suited for all wood in outdoor areas where an especially durable coating is required: timber cladding, balconies, windows and window shutters, fences, pergolas, wooden shingles, garden furniture and garden sheds, carports etc. Ideal for renewing old microporous finishes and weathered wooden surfaces.

Ingredients:

Based on natural plant oils (sunflower oil, soybean oil and thistle oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). EU limit value for this product (cat. A/e): 400 g/l VOC (2010). This product contains max. 400 g/l VOC. Detailed declaration of ingredients available upon request.

Technical Data:

Specific gravity: 1.0-1.35 g/cm³
 Viscosity: 20-60s DIN EN ISO 2431/4 mm, viscid
 Odour: faint/mild, odourless after drying
 Flashpoint: > 60 °C, acc. DIN EN ISO 2719
 pH value: not required

Storage:

5 years and longer if stored in the closed original can. If thickened by frost, store at room temperature for 24 hours prior to use.



Surface Preparation:

Wood surface must be clean, dry and frost-free (moisture content max. 20%). Osmo Country Colour is ready to use. Do not thin. Stir well before use. If possible, please apply the first coat to all sides before installation. Clean old microporous stains thoroughly. Old paints, varnishes and lacquers must be completely removed. Always wear a dust mask while sanding. If additional protection against blue stain, rot and insects is desired, pre-treat the wood if possible on all sides with Osmo WR Base Coat.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

With Osmo Flat Brush or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and spread well. Allow to dry for approx. 10-12 hours under good ventilation. After drying, apply a second coat – also thinly. When renovating, one coat applied to the clean and dry surface is usually sufficient.

Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:

Approx. 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

Coverage:

Product coverage for 1 coat is 26 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Note:

Country Colour, which has been trusted for over decades, is also available in the colour of your choice. Starting from 2.5 litres per colour tone, available in 186 RAL Classic and 1950 NCS colour tones, as well as with biocidal film protection additives. Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

Caution:

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

Disposal:

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

Colour tone:

2101 White Opaque
2203 Light Ochre Opaque
2204 Ivory Opaque
2205 Sunflower Yellow Opaque
2308 Nordic Red Opaque
2310 Cedar/Redwood Opaque
2311 Signal Red Opaque
2404 Fir Green Opaque
2501 Labrador Blue Opaque
2506 Royal Blue Opaque
2507 Dove Blue Opaque
2606 Medium Brown Opaque
2607 Dark Brown Opaque
2703 Charcoal Opaque
2704 Dusk Grey Opaque
2708 Pebble Grey Opaque
2716 Anthracite Grey Opaque
2735 Light Grey Opaque
2742 Traffic Grey A Opaque

Size:

0.75 l; 2.5 l; 25 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 10/20