

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo WR Base Coat UK

Article number: 4001

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Wood preservatives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf
 Germany

Further information obtainable from:

Product safety department
 Tel.: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

Importer

Importer for UK:
 OSMO UK,
 Smeaton Close
 Unit 24 Anglo Business Park
 Aylesbury, Bucks HP19 8UP
 Phone: 01296 481 220, www.osmouk.com
 United Kingdom

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

Additional information: For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms



GHS08 GHS09

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 1)

Signal word

Danger

Hazard-determining**components of labelling:**

aliphatic hydrocarbons, C10-C13

Hazard statements

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

Contains biocidal products: 3-Iodo-2-propynylbutylcarbamate, 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol, permethrin (ISO)

2.3 Other hazards

Always wear a dust mask when sanding.

Do not breathe spray.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13 ⚠ Asp. Tox. 1, H304, EUH066	75-100%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<5%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7 Reg.nr.: 01-2119489924-20	3-Iodo-2-propynylbutylcarbamate ⚠ Acute Tox. 3, H331; ⚠ STOT RE 1, H372; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-<1%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31






Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 2)

CAS: 107534-96-3 ELINCS: 403-640-2 Index number: 603-197-00-7 Reg.nr.: 01-0000015329-67	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol  Repr. 2, H361d;  Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=10);  Acute Tox. 4, H302	0.1-≤1%
CAS: 52645-53-1 EINECS: 258-067-9 Index number: 613-058-00-2	permethrin (ISO)  Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=1000);  Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

After inhalation:

Take affected persons out into the fresh air.
Keep warm, position comfortably and cover well.
In case of irregular breathing or respiratory arrest provide artificial respiration.
Seek medical treatment in case of complaints.
Supply fresh air and to be sure call for a doctor.
Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately remove any clothing soiled by the product.
In case of skin reactions, seek medical advice.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth.
If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 3)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

carbon dioxide (CO₂)

Formation of toxic gases is possible during heating or in case of fire.

Combustible liquid. In a fire of if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Move container from fire area if tis can be done without risk.

Use water spray to keep fire-exposed containers cool.

This material is very toxic to aquatic organismen.

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Protective equipment:

Fire-fighters should wear appropriate equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

General measures for chemical fires.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training.

Do not touch or walk through spilt material.

Do not breathe vapour/spray.

Ensure adequate ventilation

Keep away from ignition sources.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 4)

For non-emergency personnel

Wear protective clothing.

For emergency responders

No action shall be taken involving any personal risk or without suitable training.

6.2 Environmental

Wear protective equipment. Keep unprotected persons away.

precautions:

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Avoid contact with skin and eyes.

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection:

Flammable gas-air mixtures may form in empty receptacles.

Keep respiratory protective device available.

Handling:

Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 5)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Store away from foodstuffs.

Store locked up.

Store away from oxidising agents.

Further information about

storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class:

VCI storage class (VCI = German Association of the Chemical Industry): 10
10

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm
	Sk

PNECs

34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water	1.9 mg/l
PNEC fresh water	19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant	4,168 mg/l
interrupted release	190 mg/l

Additional information:

The lists valid during the making were used as basis.

Observe European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparisons with limit values and measurement strategy)

Observe European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.)

(Contd. on page 7)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 6)

8.2 Exposure controls**Appropriate engineering controls**

Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

Wash hands before breaks and at the end of work.
 Immediately remove all soiled and contaminated clothing
 Avoid contact with the eyes and skin.
 The usual precautionary measures are to be adhered to when handling chemicals.
 Store protective clothing separately.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.
 See Section 7 for information on safe handling.

Respiratory protection:

Short term filter device:
 Full mask with type ABEK filter.
 Not necessary if room is well-ventilated.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 7)

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR
 Recommended thickness of the material: ≥ 0.4 mm
 For the mixture the penetration time has to be at least 480 minutes
 (Permeation according to EN 374 Part 3: Level 6).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Eye/face protection

Recommended:
 Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Yellowish
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	170 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	> 60 °C (EG A 9/DIN EN ISO 2719)
Ignition temperature:	225 °C
Decomposition temperature:	Not determined.
pH	Mixture is non-polar/aprotic.
Viscosity:	
Kinematic viscosity at 20 °C	0.02 cm ² /s
Dynamic at 20 °C:	1.7 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.805 g/cm ³ (DIN 51757)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 8)

Relative density	Not determined.
9.2 Other information	25 mN/m (25 °C)
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

10.4 Conditions to avoid

Avoid release to the environment.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials:

No further relevant information available.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 9)

10.6 Hazardous
decomposition products: Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:
ATE (Acute Toxicity Estimates)

Inhalative	LC50 / 4h	100 mg/l
------------	-----------	----------

aliphatic hydrocarbons, C10-C13

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat) 13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (senastrum capricornutum)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	0.67 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)

107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol

Oral	LD50	1,700 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)

52645-53-1 permethrin (ISO)

Oral	LD50	1,479 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) >4,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1.5 mg/l (ATE)

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 11)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 10)

Additional toxicological information:**Acute effects (acute toxicity, irritation and corrosivity)**

May be fatal if swallowed and enters airways.

Sensitisation

Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

11.2 Information on other hazards**Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****aliphatic hydrocarbons, C10-C13**

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h >1,000 mg/l (algae)

LC50 / 96h >1,000 mg/l (fish)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h 70.2 mg/l

1,919 mg/l (Daphnia magna)

LC50 / 96h 5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

LC50 / 48h 10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50 / 48h 0.16 mg/l (Daphnia magna)

EC50/ 72h 0.022 mg/l (algae)

107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol

EC50 / 48h 2.79 mg/l (Daphnia magna)

IC50 / 72h 3.8 mg/l (algae)

IC50/ 3h 4 mg/l (algae)

LC50 / 96h 4.4 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

52645-53-1 permethrin (ISO)

IC50/ 3h 0.17 mg/l (Daphnia magna)

LC50 / 96h 0.0076 mg/l (Poecilia reticulata)

12.2 Persistence and degradability

The solvent is biodegradable.

A part of the components is heavily biodegradable.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 11)

12.5 Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects
Remark: Very toxic for fish

Behaviour in sewage processing plants:
55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50/ 96h | 0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol

EC10 | 1,890 mg/l (Bakterientoxizität)

Additional ecological information:
General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Very toxic for aquatic organisms

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Disposal must be made according to official regulations.

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents:

 Solvent naphtha
 Osmo Brush Cleaner and Thinner

SECTION 14: Transport information
**14.1 UN number or ID number
ADR, IMDG, IATA**

UN3082

**14.2 UN proper shipping name
ADR**

 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
 LIQUID, N.O.S. (PERMETHRIN)

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 12)

IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (permethrin (ISO)), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (permethrin (ISO))
14.3 Transport hazard class(es)	
ADR	
	
Class	9 (M6) Miscellaneous dangerous substances and articles.
Label	9
IMDG, IATA	
	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	
	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	
	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	(-)

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 13)

Remarks:	Chapter 3.3, special provision 375
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Remarks:	Subsection 2.10.2.7
IATA	
Remarks:	Chapter 4.4, special provision A197
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous

substances - ANNEX I

None of the ingredients is listed.

Seveso category

E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes)

for the application of lower-

tier requirements

100 t

Qualifying quantity (tonnes)

for the application of upper-

tier requirements

200 t

National regulations:

Marking in accordance with biocide guideline 98/8/EG

55406-53-6	3-Iodo-2-propynylbutylcarbamate	5.01 g/kg
107534-96-3	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol	2 g/kg
52645-53-1	permethrin (ISO)	0.6 g/kg

15.2 Chemical safety

assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reasons for alterations

Formal Changes
Reach Annex II (2021)

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version number 4.3 (replaces version 4.2)

Revision: 15.11.2022

Trade name: Osmo WR Base Coat UK

(Contd. of page 14)

Relevant phrases

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H361d Suspected of damaging the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to

Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 3: Acute toxicity – Category 3
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Repr. 2: Reproductive toxicity – Category 2
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Sources

ESIS : European chemical Substances Information System
 ECHA Portal
 Safety data sheets from raw material suppliers

*** Data compared to the previous version altered.**

Additions, Deletions, Revisions
 Updated according to regulation (EU) 2020/878 amending regulation (EC) No: 1907/2006 (UK REACH)