



## WR BASE COAT AQUA

Ready to use, liquid wood preservative!



4008 Clear



1 COAT

### Product description:

Osmo WR Base Coat<sup>Aqua</sup> is a ready-to-use waterborne wood preservative. For the protection of wood in outdoor areas without direct ground or water contact against vegetable pests such as blue stain and rot. Osmo WR Base Coat<sup>Aqua</sup> has a very low odour during application, and is odourless when dry.

### Recommended use:

Wood preservative against wood-rotting and wood-staining fungi on all exterior wood without direct ground and/or surface water contact, e.g. (not under static loads) windows, shutters, pergolas, fences, timber cladding, garden furniture, etc. Do not use indoors, except for external window frames and external doors.

Ready to use liquid wood preservative. FOR USE ONLY AS A WOOD PRESERVATIVE

### Active ingredient:

0.75% 3-iodo-2-propynyl butylcarbamate (IPBC) (7.5 g/kg); 0.24% propiconazole (ISO) (2.4 g/kg)

### Technical Data:

Specific gravity: 1.01 g/cm<sup>3</sup>

Viscosity: inviscid

Odour: faint/mild, odourless after drying

Flashpoint: > 60 °C, acc. DIN EN ISO 2719

pH value: 8.6

### Storage:

2 years and longer if stored in the closed original can.

Do not expose to frost or temperatures above 30 °C!

### Surface Preparation:

Wood surface must be clean and dry (moisture content max. 20%). Osmo WR Base Coat<sup>Aqua</sup> is ready-to-use. Please do not thin. Stir well before use.

### Methods of Application:

Coat the clean, dry and frost-free wood generously – if possible on all sides. The product should be applied evenly in order to get best results. Processing conditions: above 5°C / relative humidity below 80%.  
 - industrial use: dipping, flow-coating, spraying  
 - professional and amateur use: brush, roller, spraying.

### Cleaning of tools:

Immediately after use, with soap and water.

### Drying time:

Approx. 24 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

### Coverage:

Product coverage for 1 coat is 180-220 ml/m<sup>2</sup>. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

### Note:

Osmo WR Base Coat<sup>Aqua</sup> is not a final coat. For untreated wood, a final treatment (e.g. with Osmo wood coatings) is required within three months. Freshly treated timber must be stored after treatment under shelter or on a hard, impermeable surface to prevent direct losses to soil and water. Any losses should be collected for re-use or disposal.



## Hazard statements:

Harmful to aquatic life with long lasting effects. Contains mixture of CMIT/MIT(3:1), IPBC and propiconazole. May produce an allergic reaction.

Precautionary statements: Keep out of reach of children. Read carefully and follow all instructions. If medical advice is needed, have product container or label at hand. Avoid release to the environment. Dispose of contents/container in accordance with local regulations.

## Risk mitigation measures:

KEEP IN A SAFE PLACE. WASH HANDS AND EXPOSED SKIN before meals. 3-IODO-2-PROPYLNYL-N-BUTYL CARBAMATE is a carbamate compound which has weak anti-cholinesterase activity. DO NOT USE if under medical advice not to work with anticholinesterase compounds.

Do NOT use treated wood near surface water bodies such as lakes, streams etc. DO NOT CONTAMINATE FOODSTUFFS; EATING UTENSILS OR FOOD CONTACT SURFACES. Do not apply the product to wood or place treated wood in areas where food/feed, food utensils or food processing surfaces may come into contact with, or be contaminated by the product or treated wood. UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY. AVOID ALL CONTACT WITH PLANT LIFE. COVER ALL WATER STORAGE TANKS before application

## Disposal:

This material and its container must be disposed of safely as hazardous waste. Any product collected during application that is not re-used must be disposed of safely as hazardous waste. Do NOT empty into drains. If required, consult a professional waste operator or local authority.

European Waste Code (EWC)-Code: 03 02 05\*.

## HSE:

UK-2013-0783-0003  
MT 2013-11-29-B02  
IE/BPA 70083-001  
IS-2012-0002

Manufacturer: Troy Chemical Company B.V.,  
Poortweg 4C, NL-2612PA Delft

Colour tone:  
4008 Clear

Size:  
0.75 l; 2.5 l; 25 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 08/21