

Revision: 22.01.2024

Printing date 22.01.2024 Version number 4.0 (replaces version 3.2)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Polyx®-Oil Express

**Article number:** 3332, 3340, 3362

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

### SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements Hazard pictograms

Signal word

GHS02

Warning

GHSC

**Hazard statements** H226 Flammable liquid and vapour.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P210 Keep away from heat. - No smoking.
P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.

P501 Dispose of contents/container in accordance with national regulations.

**Additional information:** EUH210 Safety data sheet available on request.

(Contd. on page 2)



Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

Trade name: Polyx®-Oil Express

(Contd. of page 1)

**2.3 Other hazards** Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous componen	nts:	
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25–50%
EC number: 918-481-9	& Asp. Tox. 1, H304, EUH066	1
CAS: 64742-49-0	aliphatic hydrocarbons, C9-C10	≥10–<20%
EC number: 927-241-2	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	-
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	0–≤2.5%
EINECS: 252-104-2	substance with a Community workplace exposure limit	
CAS: 13463-67-7	titanium dioxide - aerodynamic diameter >10 μm	0-<2.5%
EINECS: 236-675-5		

**SVHC** Not applicable.

Additional information: Note 10: The classification as a carcinogen by inhalation applies only to

mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m. The content of Titanium dioxide varies according to the colour shade. For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

4.1 Description of first aid measures

**General information:** Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

Trade name: Polyx®-Oil Express

(Contd. of page 2)

After swallowing: Rinse mouth.

If swallowed, seek medical advice immediately and show this container or

label.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

**delayed** Headache

Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

### SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

agents: CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or

mixture Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO) carbon dioxide (CO2)

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

General measures for chemical fires.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation Keep away from ignition sources.

Wear protective clothing.

For non-emergency

personnel No action shall be taken involving any personal risk or without suitable training.

For emergency responders Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



## according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

Trade name: Polyx®-Oil Express

(Contd. of page 3)

6.2 Environmental

precautions: Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other

**sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

7.1 Precautions for safe

**handling** Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed. Prevent formation of aerosols.

Open and handle receptacle with care.

General protective and

hygienic measures: Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and

**explosion protection:** Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in

one common storage facility: Not required.

Further information about

**storage conditions:** Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)



Revision: 22.01.2024

Printing date 22.01.2024

Version number 4.0 (replaces version 3.2)

Trade name: Polyx®-Oil Express

(Contd. of page 4)

7.3 Specific end use(s)

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA | Short-term value: 1200 mg/m³

**CEFIC-HSPA** 

34590-94-8 Dipropylene glycol monomethyl ether

IOELV Long-term value: 308 mg/m³, 50 ppm

Skin

#### **DNELs**

### 34590-94-8 Dipropylene glycol monomethyl ether

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	36 mg/kgKG/Tag
Dermal	DNEL Verbraucher (Langzeit - systemische Effekte)	121 mg/cm²
Inhalative Worker (chronic - Systemic health effec)		308 mg/m³
	DNEL Verbraucher (Lanzeit - systemische Effekte)	37.2 mg/m³

#### **PNECs**

### 34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water	1.9 mg/l
PNEC fresh water	1.9 mg/l 19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant	4,168 mg/l
interrupted release	190 mg/l

Additional information:

The lists valid during the making were used as basis.

## 8.2 Exposure controls

controls

Appropriate engineering

Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

The usual precautionary measures are to be adhered to when handling

chemicals.

(Contd. on page 6)



Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

Trade name: Polyx®-Oil Express

(Contd. of page 5)

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

See Section 7 for information on safe handling.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective

device.

Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

> also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable: Nitrile rubber, NBR

Recommended thickness of the material: > 0.4 mm

For the mixture the penetration time has to be at least 480 minutes

(Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable:

Nitrile rubber, NBR Eye/face protection Tightly sealed goggles **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid

Colour: According to product specification

(Contd. on page 7)



Revision: 22.01.2024

Printing date 22.01.2024

Version number 4.0 (replaces version 3.2)

Trade name: Polyx®-Oil Express

(Contd. of page 6)

Odour: Mild

Odour threshold:Not determined.Melting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

rangeUndetermined.FlammabilityFlammable.

Lower and upper explosion limit

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Flash point: 30-35 °C (DIN EN ISO 2719)

**Decomposition temperature:** Not determined.

**pH** Mixture is non-polar/aprotic.

Viscosity:

Kinematic viscosity at 20 °C 20-25 s (DIN 53211/4mm) Kinematic viscosity at 20 °C 20-25 s (DIN 53211/4mm)

**Dynamic:** Not determined.

Solubility water:

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 10 hPa

Density and/or relative density

**Density at 20 °C:** 0.88-0.95 g/cm³ (DIN 51757)

**Relative density** Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

**Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

**VOC (EC)** < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

Change in condition

**Evaporation rate** Not determined.

Information with regard to physical hazard classes

ExplosivesVoidFlammable gasesVoidAerosolsVoidOxidising gasesVoidGases under pressureVoid

(Contd. on page 8)



Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

## Trade name: Polyx®-Oil Express

(Contd. of page 7)

Flammable liquid and vapour.	
Void	
able	
Void	
	Void Void Void Void Void Void Void Void

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

**reactions** Reacts with fabric soaked in the product (e.g. cleaning wool).

Self igniting.

**10.4 Conditions to avoid** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous

decomposition products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Formation of toxic gases is possible during heating or in case of fire.

### SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
64742-48-	9 aliphatic	hydrocarbons, C10-C13
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

(Contd. on page 9)



Revision: 22.01.2024

Printing date 22.01.2024

Version number 4.0 (replaces version 3.2)

## Trade name: Polyx®-Oil Express

(Contd. of page 8)

64742-49-	64742-49-0 aliphatic hydrocarbons, C9-C10		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50 / 4h	>20 mg/l (rat)	
34590-94-	34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>19,020 mg/kg (rat)	
		13,000–14,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	667 mg/l (rat)	
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)	

**Skin corrosion/irritation** At long or repeated contact with skin it may cause dermatitis due to the

degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met. Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

Additional toxicological

information: The product is not subject to classification according to the calculation method

of the General EU Classification Guidelines for Preparations as issued in the

latest version.

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic to	Aquatic toxicity:	
64742-48-9	aliphatic hydrocarbons, C10-C13	
EC50 / 48h	>1,000 mg/l (Daphnia magna)	
IC50 / 72h	>1,000 mg/l (algae)	
LC50 / 96h	>1,000 mg/l (fish)	
	(Contd. on page 10)	

Conta. on page 10



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

## Trade name: Polyx®-Oil Express

(Contd. of page 9)

64742-49-0 aliphatic hydrocarbons, C9-C10			
EC50 / 24h	<130 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
	>100 mg/l (selenastrum capricornutum)		
34590-94-8 Dipropylene glycol monomethyl ether			
EC50 / 48h	70.2 mg/l		
	1,919 mg/l (Daphnia magna)		
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		

12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

No further relevant information available. potential 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

### SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing

agents: Solvent naphtha

Osmo Brush Cleaner and Thinner

(Contd. on page 11)



Revision: 22.01.2024

Printing date 22.01.2024

Version number 4.0 (replaces version 3.2)

Trade name: Polyx®-Oil Express

	(Contd. of pa
SECTION 14: Transport information	
14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Oleans.	2 /F4) Flancos abla limida
Class	3 (F1) Flammable liquids.
Label 	3 
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E

(Contd. on page 12)



Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

Trade name: Polyx®-Oil Express

(Contd. of page 11)

**IMDG** 

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

maximum not quartity per outer pu

UN "Model Regulation": UN 1263 PAINT, 3, III

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU Named dangerous

substances - ANNEX INone of the ingredients is listed.Seveso categoryP5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-

tier requirements 5.000 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 50.000 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

GISBAU-Code GISCODE: Ö60

(Contd. on page 13)



## according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 4.0 (replaces version 3.2) Revision: 22.01.2024

Trade name: Polyx®-Oil Express

(Contd. of page 12)

**VOC (EC)** < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to

Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method

using substance data according to Regulation (EC) No 1272/2008.

**Department issuing SDS:** product safety department

Contact: Hr. Dr. Starp

Version number of previous

version: 3.2

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category

3

**Sources** ESIS: European chemical Substances Information System

ECHA Portal

Safety data sheets from raw material suppliers

\* Data compared to the

previous version altered. Additions, Deletions, Revisions

Updated according to regulation (EU) 2020/878 amending regulation (EC) No:

1907/2006 (REACH)