

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Polyx®-Oil Rapid

Article number: 3232 Clear satin; 3240 White transparent; 3262 Clear matt

& mixed colours

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

#### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements Hazard pictograms

CH20

GHS02

Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P210 Keep away from heat. - No smoking.
P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.
P501 Dispose of contents/container in accordance with national regulations.

(Contd. on page 2)



# according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 1)

**Additional information:** 3240: EUH211 Warning! Hazardous respirable droplets may be formed when

sprayed. Do not breathe spray or mist.

EUH210 Safety data sheet available on request.

**2.3 Other hazards** Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Must not be applied on the same spraying stand as lacquers or lacquer

corrosives that contain NC (nitrocellulose). Risk of self-ignition.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics	30–50%		
EC number: 918-481-9	er: 918-481-9   < 2 %			
	♦ Asp. Tox. 1, H304, EUH066			
CAS: 64742-49-0	aliphatic hydrocarbons, C9-C10	≥10–<20%		
EC number: 927-241-2	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412			
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	<2.5%		
EINECS: 252-104-2	substance with a Community workplace exposure limit			
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide - aerodynamic diameter >10 μm	0-2.5%		
LINEGO. 230-073-3				

**SVHC** Not applicable.

Additional information: The content of Titanium dioxide varies according to the colour shade.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m.

For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:** Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or

label

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

**delayed** Headache Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

#### SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

agents: CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or

**mixture** Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** No special measures required.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

Keep away from ignition sources.

6.2 Environmental

**precautions:** Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

(Contd. on page 4)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

# Trade name: Polyx®-Oil Rapid

(Contd. of page 3)

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other

**sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

7.1 Precautions for safe

**handling** Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed. Prevent formation of aerosols.

Open and handle receptacle with care.

General protective and

hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Information about fire - and

**explosion protection:** Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Keep respiratory protective device available.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in

one common storage facility: Not required.

Further information about

**storage conditions:** Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

**7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 5)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 4)

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

TWA | Short-term value: 1200 mg/m³

**CEFIC-HSPA** 

34590-94-8 Dipropylene glycol monomethyl ether

IOELV Long-term value: 308 mg/m³, 50 ppm

Skin

#### **PNECs**

### 34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water	190 mg/l
PNEC fresh water	190 mg/l 19 mg/l
PNEC sewage treatment plant	4,168 mg/l
PNEC1	19 mg/l
PNEC4	19 mg/l 70.2 mg/kg 4,168 mg/l
PNEC6	4,168 mg/l
PNEC8	190 mg/kg

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

**controls** No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

**Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary. Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective

device.

(Contd. on page 6)



### according to Regulation (EC) No 1907/2006, Article 31

Version number 16.0 (replaces version 15.7) Revision: 04.04.2024 Printing date 04.04.2024

Trade name: Polyx®-Oil Rapid

Hand protection Protective gloves (Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

> also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR Eye/face protection Tightly sealed goggles **Body protection:** Protective work clothing

#### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid

Colour: According to product specification

Odour: Mild

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

> 144 °C range

Lower and upper explosion limit

Lower: 0.7 Vol % Upper: 6.0 Vol %

Flash point: 45-52 °C (DIN EN ISO 2719)

Auto-ignition temperature: 240 °C

Not applicable pН

(Contd. on page 7)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 6)

Viscosity:

Kinematic viscosity at 20 °C 25-45 s (DIN EN ISO 2431/4mm)

>21 mm<sup>2</sup>/s (40°C) (calculated)

**Dynamic:** Not determined.

Solubility

water: Not miscible or difficult to mix.

Vapour pressure at 20 °C: 10 hPa

Density and/or relative density

**Density at 20 °C:** 0.88-0.95 g/cm³ (DIN 51757)

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

**Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

**VOC (EC)** < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

Information with regard to physical hazard classes

ExplosivesVoidFlammable gasesVoidAerosolsVoidOxidising gasesVoidGases under pressureVoid

Flammable liquids Flammable liquid and vapour.

Flammable solids

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Pyrophoric solids

Self-heating substances and mixtures

Void

Substances and mixtures, which emit flammable

gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoidDesensitised explosivesVoid

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

(Contd. on page 8)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 7)

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

**reactions** Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

decomposition products:

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:					
64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %					
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rat)			
Inhalative	LC50 / 4h	>5 mg/l (rat)			
64742-49-0 aliphatic hydrocarbons, C9-C10					
Oral	LD50	>2,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rat)			
Inhalative	LC50 / 4h	>20 mg/l (rat)			
34590-94-8 Dipropylene glycol monomethyl ether					
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>19,020 mg/kg (rat)			
		13,000–14,000 mg/kg (rabbit)			
Inhalative	LC50 / 4h	1,667 mg/l (rat)			
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)			

**Skin corrosion/irritation** Based on available data, the classification criteria are not met. **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisationBased on available data, the classification criteria are not met.Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.

(Contd. on page 9)



# according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

# Trade name: Polyx®-Oil Rapid

(Contd. of page 8)

STOT-single exposure STOT-repeated exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Aspiration hazard
Subacute to chronic toxicity:
Additional toxicological

Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

Additional toxicological

information: The product shows the following dangers according to the calculation method

of the General EU Classification Guidelines for Preparations as issued in the

latest version:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the

latest version

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

#### 12.1 Toxicity

_		-	-	
$\Delta \alpha$	uatic	tov	10	1 <b>†</b> \/'
$\neg u$	uauc	LUA	16	ILV.

# 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h | >1,000 mg/l (algae) LC50 / 96h | >1,000 mg/l (fish)

#### 64742-49-0 aliphatic hydrocarbons, C9-C10

EC50 / 24h <130 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

>100 mg/l (selenastrum capricornutum)

#### 34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h | 70.2 mg/l

1,919 mg/l (Daphnia magna)

LC50 / 96h | 5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

LC50 / 48h | 10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

#### 12.2 Persistence and

**degradability** No further relevant information available.

12.3 Bioaccumulative

potential No further relevant information available.12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessmentPBT: Not applicable.vPvB: Not applicable.

(Contd. on page 10)



# according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 9)

12.6 Endocrine disrupting

**properties**The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

#### European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

### **SECTION 14: Transport information**

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR 1263 PAINT IMDG, IATA PAINT

14.3 Transport hazard class(es)

**ADR** 



Class 3 (F1) Flammable liquids.

Label 3

IMDG, IATA



Class 3 Flammable liquids.

Label 3

(Contd. on page 11)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 10)

14.4 Packing group
ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No

**14.6 Special precautions for user** Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

EMS Number: F-E,S-E

Stowage Category A

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information:

**ADR** 

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**Transport category** 3 **Tunnel restriction code** D/E

**IMDG** 

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1263 PAINT, 3, III

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC Product type: PAINTS AND VARNISHES

• Product subcategory: One-pack performance coatings

· Solvent-borne coatings, Limit value: 500 g/l

VOC: <500 g/l

Directive 2012/18/EU

Named dangerous

substances - ANNEX INone of the ingredients is listed.Seveso categoryP5c FLAMMABLE LIQUIDS

(Contd. on page 12)

ΕU



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 11)

Qualifying quantity (tonnes) for the application of lower-

tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 50,000 t

REGULATION (EC) No

**1907/2006 ANNEX XVII** Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and

electronic equipment – Annex II

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing

under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

GISBAU-Code GISCODE: Ö60

**VOC (EC)** < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Department issuing SDS:** product safety department

Contact: Hr. Dr. Starp

Version number of previous

version: 15.7

(Contd. on page 13)



# according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 16.0 (replaces version 15.7) Revision: 04.04.2024

Trade name: Polyx®-Oil Rapid

(Contd. of page 12)

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category

**Sources** 

Safety data sheets from raw material suppliers

**ECHA Portal** 

ESIS: European chemical Substances Information System

\* Data compared to the previous version altered.