

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

Spray-Wax

Article number:

3009 Clear Semi-matt; 3010 Natural; 3012 White Opaque; 3013 Black Opaque; 3049 Black Opaque Matt; 3050 White Opaque Matt; 3066 White Weiß Transparent; 3084 Clear Matt; 3085 Clear Satin; 3086 Clear Gloss;

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

No further relevant information available.

Coating compound/ Surface coating/ paint
Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information obtainable from:

Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Additional information: For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms



GHS02

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

 P210 Keep away from heat. - No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves / eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 1)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

Additional information: EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards Must not be applied on the same spraying stand as lacquers or lacquer corrosives that contain NC (nitrocellulose). Risk of self-ignition. Always wear a dust mask when sanding. Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9	aliphatic hydrocarbons, C10-C13 ⚠ Asp. Tox. 1, H304, EUH066	25-50%
EC number: 927-241-2	aliphatic hydrocarbons, C9-C10 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412	10-<20%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	≤2.5%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide - aerodynamic dia meter >10 µm	0-<20%

SVHC Not applicable.

Additional information: The content of Titanium dioxide varies according to the colour shade. Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:** Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints. In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

None known.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
carbon dioxide (CO₂)

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
General measures for chemical fires.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Wear protective clothing.

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 3)

- For emergency responders** Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
 Dispose of the material collected according to regulations.
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
 Warm water and cleansing agent
- 6.4 Reference to other sections** See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Use only in well ventilated areas.
- Keep away from heat and direct sunlight.
- Keep receptacles tightly sealed.
- Prevent formation of aerosols.
- Open and handle receptacle with care.

General protective and hygienic measures:

- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Do not eat, drink, smoke or sniff while working.
- Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Handling:

- Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

- Store only in the original receptacle.
- Store in a cool location.

Information about storage in one common storage facility:

- Not required.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 4)

Further information about storage conditions:

Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Protect from frost.

Storage class:

3

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****aliphatic hydrocarbons, C10-C13**

TWA	Short-term value: 1200 mg/m ³ CEFIC-HSPA
-----	--

34590-94-8 Dipropylene glycol monomethyl ether

IOELV	Long-term value: 308 mg/m ³ , 50 ppm Skin
-------	---

DNELs**34590-94-8 Dipropylene glycol monomethyl ether**

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	36 mg/kg KGew. /Tag
Dermal	DNEL Verbraucher (Langzeit - systemische Effekte)	121 mg/cm ²
Inhalative	Worker (chronic - Systemic health effec)	308 mg/m ³
	DNEL Verbraucher (Lanzzeit - systemische Effekte)	37.2 mg/m ³

PNECs**34590-94-8 Dipropylene glycol monomethyl ether**

PNEC sea water	1.9 mg/l
PNEC fresh water	19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant interrupted release	4,168 mg/l 190 mg/l

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Appropriate engineering controls**

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 5)

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

Wash hands before breaks and at the end of work.
 Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Immediately remove all soiled and contaminated clothing
 Do not inhale gases / fumes / aerosols.
 The usual precautionary measures are to be adhered to when handling chemicals.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.
 See Section 7 for information on safe handling.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.
 Not necessary if room is well-ventilated.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.

Hand protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
 To avoid skin problems reduce the wearing of gloves to the required minimum.
 Protective gloves

Material of gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
 As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR
 Recommended thickness of the material: ≥ 0.4 mm
 For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
 Tightly sealed goggles

Eye/face protection

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 6)

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information**

Physical state	Fluid
Colour:	According to product specification
Odour:	Mild
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	144 °C
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	7 Vol %
Flash point:	23 - 60 °C (DIN EN ISO 2719)
Ignition temperature:	240 °C
Decomposition temperature:	Not determined.
pH	Mixture is non-polar/aprotic.
Viscosity:	
Kinematic viscosity at 40 °C	>21 mm ² /s
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	10 hPa
Density and/or relative density	
Density at 20 °C:	0.9–1.1 g/cm ³ (DIN 51757)
Relative density	Not determined.

9.2 Other information**Appearance:****Form:** Viscous**Important information on protection of health and environment, and on safety.****Auto-ignition temperature:** Product is not selfigniting.**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Solvent separation test:** < 3 % (ADR 2.2.3.1.4 f)**Solvent content:****VOC (EC)** < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 7)

Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
10.3 Possibility of hazardous reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products:	Carbon monoxide and carbon dioxide Nitrogen oxides (NO _x) Formation of toxic gases is possible during heating or in case of fire.
Additional information:	Must not be applied on the same spraying stand as lacquers or lacquer corrosives that contain NC (nitrocellulose). Risk of self-ignition.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 8)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

aliphatic hydrocarbons, C10-C13

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

aliphatic hydrocarbons, C9-C10

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	>20 mg/l (rat)

13463-67-7 titanium dioxide - aerodynamic dia meter >10 µm

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat) 13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (senastrum capricornutum)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 9)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

aliphatic hydrocarbons, C10-C13

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h >1,000 mg/l (algae)

LC50 / 96h >1,000 mg/l (fish)

aliphatic hydrocarbons, C9-C10

EC50 / 24h <130 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

>100 mg/l (senastrum capricornutum)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h 70.2 mg/l

1,919 mg/l (Daphnia magna)

LC50 / 96h 5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

LC50 / 48h 10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

12.2 Persistence and

degradability

No further relevant information available.

12.3 Bioaccumulative

potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 11)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 10)

15 01 10* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:**

Water, if necessary together with cleansing agents.
 Solvent naphtha
 Osmo Brush Cleaner and Thinner

SECTION 14: Transport information**14.1 UN number or ID number****ADR, IMDG, IATA** UN1263**14.2 UN proper shipping name****ADR** 1263 PAINT**IMDG, IATA** PAINT**14.3 Transport hazard class(es)****ADR****Class** 3 (F1) Flammable liquids.**Label** 3**IMDG, IATA****Class** 3 Flammable liquids.**Label** 3**14.4 Packing group****ADR, IMDG, IATA** III**14.5 Environmental hazards:****Marine pollutant:** No**14.6 Special precautions for user**

Warning: Flammable liquids.

Hazard identification number (Kemler code): 30**EMS Number:** F-E,S-E**Stowage Category** A**14.7 Maritime transport in bulk according to IMO****instruments** Not applicable.**Transport/Additional information:****ADR****Limited quantities (LQ)** 5L

(Contd. on page 12)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 11)

Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
<hr/>	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2004/42/EC**

Product type: PAINTS AND VARNISHES

- Product subcategory: One-pack performance coatings
 - Solvent-borne coatings, Limit value: 500 g/l
- VOC: <500 g/l

Directive 2012/18/EU**Named dangerous substances - ANNEX I**

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements

5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 12)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:**VOC (EC)** < 500 g/l (VOC-max. = 500 g/l (2010 A/i))**15.2 Chemical safety****assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reasons for alterations Reach Annex II (2021)
Relevant phrases H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to**Regulation (EC) No 1272/2008** The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.**Department issuing SDS:** product safety department**Contact:** Hr. Dr. Starp**Version number of previous version:** 3.1

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.07.2022

Version number 3.3 (replaces version 3.1)

Revision: 26.01.2022

Trade name: Spray-Wax

(Contd. of page 13)

Sources

Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
ESIS : European chemical Substances Information System
ECHA Portal
Safety data sheets from raw material suppliers

*** Data compared to the previous version altered.**

Additions, Deletions, Revisions
Updated according to regulation (EU) 2020/878 amending regulation (EC) No: 1907/2006 (REACH)

EU