

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Natural Oil Woodstain**

Article number: 701 Clear

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint
Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information

obtainable from: Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Additional information: For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms Void

Signal word Void

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with national regulations.

Additional information: EUH208 Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

Contains biocidal products: 3-Iodo-2-propynylbutylcarbamate

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 1)

2.3 Other hazards

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-48-9 EC number: 918-481-9	aliphatic hydrocarbons, C10-C13 ----- ☠ Asp. Tox. 1, H304, EUH066	30–50%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	3-<10%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-Iodo-2-propynylbutylcarbamate ☠ Acute Tox. 2, H330; ☠ STOT RE 1, H372; ☠ Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ☠ Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.1–<0.25%

SVHC Not applicable.

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

Do NOT induce vomiting.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
carbon dioxide (CO₂)

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
General measures for chemical fires.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.
Wear protective clothing.

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training.

For emergency responders

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 3)

6.3 Methods and material for
containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Avoid contact with skin and eyes.

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection:

Keep respiratory protective device available.

Handling:

Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:** Store only in the original receptacle.**Information about storage in****one common storage facility:** Not required.**Further information about****storage conditions:**

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class:VCI storage class (VCI = German Association of the Chemical Industry): 10
10**7.3 Specific end use(s)**

No further relevant information available.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA	Short-term value: 1200 mg/m ³ CEFIC-HSPA
-----	--

34590-94-8 Dipropylene glycol monomethyl ether

IOELV	Long-term value: 308 mg/m ³ , 50 ppm Skin
-------	---

DNELs

34590-94-8 Dipropylene glycol monomethyl ether

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	36 mg/kgKG/Tag
Dermal	DNEL Verbraucher (Langzeit - systemische Effekte)	121 mg/cm ²
Inhalative	Worker (chronic - Systemic health effec)	308 mg/m ³
	DNEL Verbraucher (Lanzeit - systemische Effekte)	37.2 mg/m ³

PNECs

34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water	1.9 mg/l
PNEC fresh water	19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant interrupted release	4,168 mg/l 190 mg/l

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing
 Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Do not inhale gases / fumes / aerosols.
 The usual precautionary measures are to be adhered to when handling chemicals.
 Do not eat, drink, smoke or sniff while working.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 5)

Respiratory protection:

Do not carry product impregnated cleaning cloths in trouser pockets.
See Section 7 for information on safe handling.
Use suitable respiratory protective device only when aerosol or mist is formed.
Not necessary if room is well-ventilated.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.4 mm
For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 6)

Colour:	Colourless
Odour:	Mild
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	> 180 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Flash point:	> 61 °C (DIN EN ISO 2719)
Auto-ignition temperature:	240 °C
Decomposition temperature:	Not determined.
pH	Mixture is non-polar/aprotic.
Viscosity:	
Kinematic viscosity at 20 °C	25-35 s (DIN EN ISO 2431/4mm) >21 mm ² /s (40°C) (calculated)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.97-0.99 g/cm ³ (DIN 51757)
Relative density	Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Solvent content:

VOC (EC) <400 g/l

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void

Flammable gases Void

Aerosols Void

Oxidising gases Void

Gases under pressure Void

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 7)

Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
10.3 Possibility of hazardous reactions	Reacts with fabric soaked in the product (e.g. cleaning wool). Reacts with acids, alkalis and oxidising agents.
10.4 Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products:	Carbon monoxide and carbon dioxide Nitrogen oxides (NO _x) Formation of toxic gases is possible during heating or in case of fire.
Additional information:	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50 / 4h	50 mg/l
------------	-----------	---------

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 8)

64742-48-9 aliphatic hydrocarbons, C10-C13		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)
34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat) 13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (senastrum capricornutum)
55406-53-6 3-Iodo-2-propynylbutylcarbamate		
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	0.67 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

Additional toxicological

information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

Sensitisation Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 9)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h	>1,000 mg/l (Daphnia magna)
IC50 / 72h	>1,000 mg/l (algae)
LC50 / 96h	>1,000 mg/l (fish)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h	70.2 mg/l 1,919 mg/l (Daphnia magna)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50 / 48h	0.16 mg/l (Daphnia magna)
EC50/ 72h	0.022 mg/l (algae)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to aquatic life with long lasting effects.
Harmful to fish

Behaviour in sewage processing plants:

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50/ 96h	0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
-----------	--

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 10)

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Recommended cleansing agents:

Solvent naphtha

Osmo Brush Cleaner and Thinner

SECTION 14: Transport information**14.1 UN number or ID number****ADR, ADN, IMDG, IATA**

Not applicable

14.2 UN proper shipping name**ADR**

Not applicable

ADN, IMDG, IATA

Not applicable

14.3 Transport hazard class(es)**ADR, ADN, IMDG, IATA****Class**

Not applicable

14.4 Packing group**ADR, IMDG, IATA**

Not applicable

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user

Not applicable.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

UN "Model Regulation":

Not applicable

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 11)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous****substances - ANNEX I**

None of the ingredients is listed.

REGULATION (EC) No**1907/2006 ANNEX XVII**

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:**Marking in accordance with biocide guideline 98/8/EG**

55406-53-6 | 3-Iodo-2-propynylbutylcarbamate

1 g/kg

VOC (EC)

< 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety**assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 20.1 (replaces version 20.0)

Revision: 11.12.2023

Trade name: Natural Oil Woodstain

(Contd. of page 12)

H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Recommended restriction of use

Keep out of the reach of children

Classification according to

Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Date of previous version:

07.02.2020

Version number of previous

version:

20.0

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route
 (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

ESIS : European chemical Substances Information System
 ECHA Portal
 Safety data sheets from raw material suppliers

*** Data compared to the previous version altered.**

Additions, Deletions, Revisions
 Updated according to regulation (EU) 2020/878 amending regulation (EC) No: 1907/2006 (REACH)