

Revision: 31.03.2023

Printing date 21.08.2023 Version number 21.0 (replaces version 20.2)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Natural Oil Woodstain

Article number: 700 Pine, 702 Larch, 703 Mahogany, 706 Oak, 707 Walnut, 708 Teak, 710

Stone Pine, 712 Ebony, 727 Rosewood, 728 Red Cedar, 729 Fir Green, 731 Oregon Pine, 732 Light Oak, 900 White, 903 Basalt Grey, 905 Patina, 906

Pearl Grey, 907 Quartz Grey & mixed colour shades

1.2 Relevant identified uses of the substance or mixture

and uses advised against

No further relevant information available.

Application of the substance

/ the mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms Void Signal word Void

**Hazard statements** H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with national regulations.

Additional information: EUH208 Contains 3-lodo-2-propynylbutylcarbamate. May produce an allergic

reaction.

(Contd. on page 2)



## according to 1907/2006/EC, Article 31

Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

Trade name: Natural Oil Woodstain

(Contd. of page 1)

**2.3 Other hazards** Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 918-481-9	aliphatic hydrocarbons, C10-C13	25-50%
	& Asp. Tox. 1, H304, EUH066	
CAS: 55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0.1–<0.25%
EINECS: 259-627-5	Acute Tox. 2, H330; 🚯 STOT RE 1, H372; 🕎 Eye Dam. 1,	
Index number: 616-212-00-7	Acute Tox. 2, H330; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,	
	H410 (M=10);	

**SVHC** Not applicable.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

The content of Titanium dioxide varies according to the colour shade.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

After swallowing: Rinse mouth.

If swallowed, seek medical advice immediately and show this container or

label.

Do NOT induce vomiting.

(Contd. on page 3)



Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

Trade name: Natural Oil Woodstain

(Contd. of page 2)

**4.2 Most important symptoms and effects, both acute and** 

**delayed** Headache Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

### SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or

*mixture* carbon dioxide (CO2)

Carbon monoxide (CO)

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

General measures for chemical fires.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

Wear protective clothing.

For non-emergency

personnel No action shall be taken involving any personal risk or without suitable training.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.6. Environmental

6.2 Environmental

precautions: Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

## Trade name: Natural Oil Woodstain

(Contd. of page 3)

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other

sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

7.1 Precautions for safe

handling Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols. Avoid contact with skin and eyes.

General protective and

hygienic measures: Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and

explosion protection: Keep respiratory protective device available.

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

**storerooms and receptacles:** Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

Further information about

Store receptacle in a well ventilated area. storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class:

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)



Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

Trade name: Natural Oil Woodstain

(Contd. of page 4)

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

TWA Short-term value: 1200 mg/m³

CEFIC-HSPA

**Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls
Appropriate engineering

*controls* Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols.

The usual precautionary measures are to be adhered to when handling

chemicals.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

See Section 7 for information on safe handling.

**Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective

device.

Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

## Trade name: Natural Oil Woodstain

(Contd. of page 5)

Penetration time of glove

material The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR Eye/face protection Tightly sealed goggles **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: According to product specification

Odour:

Odour threshold: Not determined. Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

> 180 °C range **Flammability** Not applicable.

Lower and upper explosion limit

0.6 Vol % Lower: 7.0 Vol % Upper:

> 61 °C (DIN EN ISO 2719) Flash point:

Auto-ignition temperature: 240 °C

Decomposition temperature: Not determined.

pН Mixture is non-polar/aprotic.

Viscosity:

Kinematic viscosity at 20 °C 30-60 s (DIN EN ISO 2431/3mm)

>21 mm<sup>2</sup>/s (40°C) (calculated)

Dynamic: Not determined.

Solubility

water: Not miscible or difficult to mix.

Not determined. Partition coefficient n-octanol/water (log value) Vapour pressure: Not determined.

(Contd. on page 7)



Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

Trade name: Natural Oil Woodstain

(Contd. of page 6)

Density and/or relative density

**Density at 20 °C:** 0.96-1.05 g/cm³ (DIN 51757)

Relative density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

**Ignition temperature:** Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Solvent content:

**VOC (EC)** <400 g/l

Change in condition

**Evaporation rate** Not determined.

Information with regard to physical hazard classes

**Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Void Pyrophoric liquids Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

10.2 Chemical stability
Thermal decomposition /
conditions to be avoided:

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

**reactions** Reacts with fabric soaked in the product (e.g. cleaning wool).

Reacts with acids, alkalis and oxidising agents.

(Contd. on page 8)



Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

Trade name: Natural Oil Woodstain

(Contd. of page 7)

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous

Carbon monoxide and carbon dioxide decomposition products:

Nitrogen oxides (NOx)

Formation of toxic gases is possible during heating or in case of fire.

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

## SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. Acute toxicity

LD/LC50 values	relevant for	classification:
ED/ECOU Values	I CIC V allt I OI	CIUSSIIICUUII.

#### **ATE (Acute Toxicity Estimates)**

Inhalative LC50 / 4h 50 mg/l

aliphatic hydrocarbons, C10-C13
---------------------------------

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

### 55406-53-6 3-lodo-2-propynylbutylcarbamate

Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

Inhalative LC50 / 4h 0.67 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)

Based on available data, the classification criteria are not met. Skin corrosion/irritation Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

Subacute to chronic toxicity:

Additional toxicological

information: The product shows the following dangers according to the calculation method

of the General EU Classification Guidelines for Preparations as issued in the

latest version:

(Contd. on page 9)



Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

## Trade name: Natural Oil Woodstain

(Contd. of page 8)

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic to	cicity:	
aliphatic hy	aliphatic hydrocarbons, C10-C13	
EC50 / 48h	>1,000 mg/l (Daphnia magna)	
IC50 / 72h	>1,000 mg/l (algae)	
LC50 / 96h	>1,000 mg/l (fish)	
	3-lodo-2-propynylbutylcarbamate	

EC50 / 48h 0.16 mg/l (Daphnia magna)

EC50/ 72h | 0.022 mg/l (algae)

### 12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential No further relevant information available.12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessmentPBT: Not applicable.vPvB: Not applicable.

12.6 Endocrine disrupting

**properties** The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

**Remark:** Harmful to aquatic life with long lasting effects.

Harmful to fish

#### Behaviour in sewage processing plants:

#### 55406-53-6 3-lodo-2-propynylbutylcarbamate

EC50/ 96h | 0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

#### Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 10)



Revision: 31.03.2023

Printing date 21.08.2023 Version number 21.

Version number 21.0 (replaces version 20.2)

Trade name: Natural Oil Woodstain

(Contd. of page 9)

Harmful to aquatic organisms

## SECTION 13: Disposal considerations

13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

Disposal must be made according to official regulations.

European	European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing

agents: Solvent naphtha

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Not applicable	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Not applicable	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Not applicable	
14.4 Packing group		
ADR, IMDG, IATA	Not applicable	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Not applicable	

(Contd. on page 11)



Revision: 31.03.2023

Printing date 21.08.2023 Version number 21.0 (replaces version 20.2)

Trade name: Natural Oil Woodstain

(Contd. of page 10)

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC Product type: PAINTS AND VARNISHES

• Product subcategory: Interior/exterior trim varnishes and woodstains,

including opaque woodstains

· Solvent-borne coatings, Limit value: 400 g/l

VOC: <400 g/l

Directive 2012/18/EU
Named dangerous

substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

Name of the Course Points to Part of

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Marking in accordance with biocide guideline 98/8/EG

55406-53-6 3-lodo-2-propynylbutylcarbamate

1 g/kg

**VOC (EC)** < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)



## according to 1907/2006/EC, Article 31

Printing date 21.08.2023 Version number 21.0 (replaces version 20.2) Revision: 31.03.2023

## Trade name: Natural Oil Woodstain

(Contd. of page 11)

Relevant phrases H302 Harmful if swallowed.

> H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to

Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method

using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Version number of previous

version: 20.2

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category

ESIS: European chemical Substances Information System

**ECHA Portal** 

Safety data sheets from raw material suppliers

\* Data compared to the

Sources

previous version altered. Additions, Deletions, Revisions

Updated according to regulation (EU) 2020/878 amending regulation (EC) No:

1907/2006 (REACH)