

#### according to 1907/2006/EC, Article 31

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: UV-Protection-Oil Tints

Article number: 424 Spruce, 425 Oak, 426 Larch, 427 Douglas, 428 Cedar, 429 Natural,

431 Light Red Cedar, 432 Light Oak

& mixed colours

1.2 Relevant identified uses of the substance or mixture

and uses advised against

No further relevant information available.

Application of the substance

/ the mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms Void Signal word Void

**Hazard statements** H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with national regulations.

Additional information: EUH208 Contains 3-lodo-2-propynylbutylcarbamate. May produce an allergic

reaction.

(Contd. on page 2)



Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

Trade name: UV-Protection-Oil Tints

(Contd. of page 1)

EUH210 Safety data sheet available on request.

Contains biocidal products: 3-lodo-2-propynylbutylcarbamate

2.3 Other hazards Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	20-40%
EC number: 918-481-9	& Asp. Tox. 1, H304, EUH066	
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	10-<25%
EINECS: 252-104-2	substance with a Community workplace exposure limit	
CAS: 127519-17-9	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-	<3%
ELINCS: 407-000-3	benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]	
Index number: 607-281-00-4	propionates	
	Aquatic Chronic 2, H411	
CAS: 55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0.1–<0.25%
EINECS: 259-627-5	Acute Tox. 2, H330; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,	
Index number: 616-212-00-7	H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,	
	H410 (M=10); • Acute Tox. 4, H302; Skin Sens. 1, H317	

**SVHC** Not applicable.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

After inhalation:

**General information:** Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product. Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 3)



## according to 1907/2006/EC, Article 31

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

Trade name: UV-Protection-Oil Tints

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

After swallowing: Rinse mouth.

If swallowed, seek medical advice immediately and show this container or

label.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

**delayed** Headache Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

### SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

For safety reasons unsuitable

extinguishing agents:

•...

5.2 Special hazards arising

from the substance or

mixture Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO) carbon dioxide (CO2)

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

For this mixture there are no extinguishing agent restrictions.

General measures for chemical fires.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

Wear protective clothing.

For non-emergency

personnel No action shall be taken involving any personal risk or without suitable training.

(Contd. on page 4)



## according to 1907/2006/EC, Article 31

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

Trade name: UV-Protection-Oil Tints

(Contd. of page 3)

For emergency responders

6.2 Environmental

precautions:

Wear protective equipment. Keep unprotected persons away.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Warm water and cleansing agent

6.4 Reference to other

**sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

7.1 Precautions for safe

**handling** Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

General protective and

hygienic measures: Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and

**explosion protection:** Keep respiratory protective device available.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Handling: Even a small sip can lead to life-threatening damage to the lungs. Keep rags

filled with this liquid out of the reach of children.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

(Contd. on page 5)



Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

Trade name: UV-Protection-Oil Tints

(Contd. of page 4)

Further information about

**storage conditions:** Store receptacle in a well ventilated area.

Protect from frost.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**Storage class:** VCI storage class (VCI = German Association of the Chemical Industry): 10

10

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

	Ingredients with	ı limit values that re	quire monitorin	g at the workplace:
--	------------------	------------------------	-----------------	---------------------

### 64742-48-9 aliphatic hydrocarbons, C10-C13

TWA Short-term value: 1200 mg/m³

**CEFIC-HSPA** 

#### 34590-94-8 Dipropylene glycol monomethyl ether

IOELV Long-term value: 308 mg/m³, 50 ppm

Skin

#### DNELs

#### 34590-94-8 Dipropylene glycol monomethyl ether

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	36 mg/kgKG/Tag
Dermal	DNEL Verbraucher (Langzeit - systemische Effekte)	121 mg/cm <sup>2</sup>
Inhalative	Worker (chronic - Systemic health effec)	308 mg/m <sup>3</sup>
	DNEL Verbraucher (Lanzeit - systemische Effekte)	37.2 mg/m³

#### **PNECs**

#### 34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water	1.9 mg/l
PNEC fresh water	19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant	4,168 mg/l
interrupted release	190 mg/l

**Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls
Appropriate engineering

controls Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 6)



Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

Trade name: UV-Protection-Oil Tints

(Contd. of page 5)

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

The usual precautionary measures are to be adhered to when handling

chemicals.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

See Section 7 for information on safe handling.

**Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective

device.

Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary.

**Hand protection** Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4 \text{ mm}$ 

For the mixture the penetration time has to be at least 480 minutes

(Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable: Eye/face protection

Nitrile rubber, NBR

Tightly sealed goggles

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

Trade name: UV-Protection-Oil Tints

(Contd. of page 6)

**Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid

Colour: According to product specification

Odour: Mild

Odour threshold: Not determined. Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

> 180 °C range **Flammability** Not applicable.

Lower and upper explosion limit

0.7 Vol % Lower: Upper: 14.0 Vol %

≥ 63 °C (DIN EN ISO 2719) Flash point:

Auto-ignition temperature: Undetermined Decomposition temperature: Not determined.

pН Mixture is non-polar/aprotic.

Viscosity:

Kinematic viscosity at 20 °C 60-80 s (DIN EN ISO 2431/4 mm)

>21 mm<sup>2</sup>/s (40°C) (calculated)

Dynamic: Not determined.

Solubility water:

Fully miscible.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 0.4 hPa

Density and/or relative density

Density at 20 °C: 0.9-1.0 g/cm3 (DIN 51757)

Relative density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

(Contd. on page 8)



Revision: 14.12.2023

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4)

Trade name: UV-Protection-Oil Tints

(Contd. of page 7)

Solvent content:

< 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l) VOC (EC)

378 g/l

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

**Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable

gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void Desensitised explosives Void

### SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous

decomposition products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Formation of toxic gases is possible during heating or in case of fire.

Additional information: Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

(Contd. on page 9)



Revision: 14.12.2023

Printing date 14.12.2023

Version number 4.0 (replaces version 3.4)

Trade name: UV-Protection-Oil Tints

(Contd. of page 8)

## **SECTION 11: Toxicological information**

64742-48-9 aliphatic hydrocarbons, C10-C13

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values releva	ant for classification:
ATE (Acute Toxicity E	stimates)
Inhalative LC50 / 4h	45.8 mg/l

on in the damping of the one		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)
34590-94-	8 Dipropyle	ne glycol monomethyl ether
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat)
		13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)
55406-53-6 3-lodo-2-propynylbutylcarbamate		
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	0.67 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

Subacute to chronic toxicity: Additional toxicological information:

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the

latest version.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

## Trade name: UV-Protection-Oil Tints

(Contd. of page 9)

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity:			
64742-48-9 alip	64742-48-9 aliphatic hydrocarbons, C10-C13		
EC50 / 48h	>1,000 mg/l (Daphnia magna)		
IC50 / 72h	>1,000 mg/l (algae)		
LC50 / 96h	>1,000 mg/l (fish)		
34590-94-8 Dip	ropylene glycol monomethyl ether		
EC50 / 48h	70.2 mg/l		
	1,919 mg/l (Daphnia magna)		
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
127519-17-9 A ı	127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-		
eth	ethyl)-4-hydroxyphenyl]propionates		
EC50 / 48h	3.2 mg/l (Daphnia magna) (24h EC 50 acute immobilisation test)		
Bioconceived fa	Bioconceived factor <3 (Flow-through fish test)		
55406-53-6 3-lodo-2-propynylbutylcarbamate			
EC50 / 48h	0.16 mg/l (Daphnia magna)		
EC50/ 72h	0.022 mg/l (algae)		

#### 12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential No further relevant information available.12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessmentPBT: Not applicable.vPvB: Not applicable.

12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

**Remark:** Harmful to aquatic life with long lasting effects.

Harmful to fish

(Contd. on page 11)



Revision: 14.12.2023

Printing date 14.12.2023

Version number 4.0 (replaces version 3.4)

Trade name: UV-Protection-Oil Tints

(Contd. of page 10)

Behaviour in sewage processing plants:

55406-53-6 3-lodo-2-propynylbutylcarbamate

EC50/ 96h | 0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 01 11\* | waste paint and varnish containing organic solvents or other hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing

agents: Water, if necessary together with cleansing agents.

Solvent naphtha

Osmo Brush Cleaner and Thinner

### SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG, IATA Not applicable

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Not applicable

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Not applicable

14.4 Packing group

ADR, IMDG, IATA Not applicable

(Contd. on page 12)



Revision: 14.12.2023

Printing date 14.12.2023

Version number 4.0 (replaces version 3.4)

Trade name: UV-Protection-Oil Tints

(Contd. of page 11)

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Not applicable.

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

**UN "Model Regulation":** Not applicable

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC Product type: PAINTS AND VARNISHES

• Product subcategory: Interior/exterior trim varnishes and woodstains,

including opaque woodstains

· Solvent-borne coatings, Limit value: 400 g/l

VOC: <400 g/l

Directive 2012/18/EU

Named dangerous

substances - ANNEX I

None of the ingredients is listed.

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and

electronic equipment - Annex II

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing

under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and

third countries in drug precursors

None of the ingredients is listed.

National regulations:

Marking in accordance with biocide guideline 98/8/EG

55406-53-6 3-lodo-2-propynylbutylcarbamate

1.09 g/kg

(Contd. on page 13)



## according to 1907/2006/EC, Article 31

Printing date 14.12.2023 Version number 4.0 (replaces version 3.4) Revision: 14.12.2023

## Trade name: UV-Protection-Oil Tints

(Contd. of page 12)

VOC (EC)

< 400 g/I (VOC-max. Cat A/e (2010) = 400 g/I)

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to

Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method

using substance data according to Regulation (EC) No 1272/2008.

**Department issuing SDS:** product safety department

Contact: Hr. Dr. Starp
Date of previous version: 27.05.2020

Version number of previous

version: 3.4

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

(Contd. on page 14)



Revision: 14.12.2023

Printing date 14.12.2023

Version number 4.0 (replaces version 3.4)

## Trade name: UV-Protection-Oil Tints

(Contd. of page 13)

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category

1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category

2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category

3

**Sources** ESIS: European chemical Substances Information System

ECHA Portal

Safety data sheets from raw material suppliers

\* Data compared to the

previous version altered. Additions, Deletions, Revisions

Updated according to regulation (EU) 2020/878 amending regulation (EC) No:

1907/2006 (REACH)

EU -