



# CHOPPING BOARD OIL

**Oil-wax wood coating**



3099 Clear  
Matt



## Product description:

Clear oil-wax combination for wooden chopping boards. Osmo Chopping Board Oil is based on natural plant oils and waxes. Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160). Osmo Chopping Board Oil is food safe acc. EN 1186 Part 5 / 14.

## Recommended use:

Osmo Chopping Board Oil is ideal for the protection of wooden chopping boards.

## Ingredients:

Based on natural plant oils (sunflower, soybean and thistle oils) and waxes, paraffin, lead-free siccatives (drying agents) and water-repellent additives. Dearomatised white spirit (benzene-free). Detailed declaration of ingredients available upon request.

## Technical data:

Specific weight: 0.92-0.97 g/cm<sup>3</sup>

Viscosity: 50-70s DIN EN ISO 2431/4 mm, thixotropic

Odour: faint/mild, odourless after drying

Flashpoint: > 60°C, acc. DIN EN ISO 2719

## Storage:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

## Surface preparation:

Wood surface must be clean, dry and frost-free (moisture content max. 18%). Osmo Chopping Board Oil is ready to use. Do not thin. Stir well before use. Clean old microporous stains thoroughly. Old paints, varnishes and lacquers must be completely removed. Always wear a dusk mask while sanding. Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work P150-240 (depending on wood species). Before oiling the surface, remove sanding dust with a broom or vacuum cleaner.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

## Methods of Application:

Apply the first coat thinly along the wood grain with an Osmo Microfibre Roller, Flat Brush or Osmo Coating Applicator Fleece. Allow to dry for approx. 8-10 hours. Ventilate well while drying. Apply the second coat with an Osmo Coating Applicator Fleece or a lint-free cloth. For renovations, one coat applied to the clean and dry surface with an Coating Applicator Fleece or lint-free cloth is usually sufficient.

## Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

## Drying time:

Approx. 8-10 hours (normal climatic conditions, 20-23°C/ 50-65% rel. humidity). Ventilate well while



drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

**Coverage:**

Product coverage for 1 coat is 30 m<sup>2</sup>/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

**Recommendation:**

Ready to use - do not thin! Apply thinly with Osmo Flat Brush, Finish Applicator Fleece or Microfibre Roller to the clean wood surface. The coating results vary depending on the wood moisture content (max. 18%) and the condition of the wood, along with other factors. Therefore, a trial application should always be carried out - especially on unknown substrates!

**Note:**

Osmo Chopping Board Oil Clear enhances the wood colour (permanent wet effect). Applying the product too generously and insufficient ventilation lead to delays in drying time. Surfaces treated with Osmo Chopping Board Oil can be cleaned effortlessly with a damp cloth; afterwards rub dry.

**Caution:**

Keep out of reach of children. Safety data sheet available on request. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. EU VOC limit value for this product: out of scope.

**Disposal:**

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

**Colour tone:**

3099 Clear Matt

**Size:**

0.5 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any previous product information.

Version 01/26