



2K WOOD OIL

For high traffic wooden flooring and parquet



6100 Clear Matt 6111 White Matt 6112 Silver Grey Matt 6114 Graphite Matt 6118 Light Grey Matt



6116 Cherry Matt 6119 Natural Matt 6138 Garnet Matt 6141 Havanna Matt 6143 Cognac Matt



6164 Tobacco Matt 6190 Black Matt



Product description:

Osmo 2K Wood Oil is a high-quality solvent-free matt 2-component oil based on natural oils for professional use. It produces a microporous and breathable surface with only one coat.. Resistant to wine, beer, cola, coffee, water, etc. acc. German DIN 12720 (formerly 68861-1C). When dry, the coating is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

Recommended use:

Osmo 2K Wood Oil is suitable for all parquet and wooden flooring (solid wood, plank, strip, stairs, etc.) acc. German DIN 18356 as well as furniture surfaces. Especially suitable for oily and resinous hardwoods and commercial interiors, which require the use of a solvent-free product.

Ingredients:

Based on natural plant oils (linseed oil), waxes, siccatives (drying agents) and water repellent additives. Colour pigmented 2K Wood Oil also contains iron oxide and organic pigments as well as titanium dioxide as white pigment. Detailed declaration of ingredients available upon request.

Technical data:

Specific weight: 0.95-1.20 g/cm³

Viscosity: 40-140s (4 mm, DIN 53211)

Odour: faint/mild, odourless after drying

Flashpoint: > 100 °C, acc. DIN EN ISO 2719

Storage:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use. Leftover mixed product cannot be stored and reused.

Surface preparation:

Osmo 2K Wood Oil is not ready to use. Shortly before the application, add the hardener (mixing ratio 100:12 vol.-%) and mix both components thoroughly. Do not thin. Pot time is approx. 3-4 hours. Wood surface must be clean, sanded, dry and frost-free (moisture content max. 20%). Clean old microporous stains thoroughly. Old paints, varnishes and lacquers must be completely removed. Always wear a dust mask while sanding. Fill small cracks, larger joints or holes in wood (Osmo Wood Filler or Osmo Wood Putty 7350). Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work, clear: for flooring P100-120, for furniture P120-180. Final sanding work, coloured: for an intense colour and more surefootedness at least grit P100. For a harmonious colour grit P120-150. For furniture grit P120-180. Before oiling the surface, remove sanding dust with a broom or vacuum cleaner.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.



Methods of Application:

Apply 2K Wood Oil thinly with Osmo Double Blade Scraper. On chamfered flooring, apply 2K Wood Oil in sections thinly with Osmo Microfibre Roller, without filling the joints. Wait approx. 20-40 minutes for the oil to penetrate the wood. Afterwards buff oil into wood and even out the surface with a single disc machine and a white or beige pad (or ideally on furniture with Osmo HandXcenter and a white pad). Leave the surface to dry. Note: If the pad leaves streaks due to too much product, we recommend turning over the pad or replacing it. To prevent a possible pressure build-up in the container, allow oil and hardener mixtures to completely react before closing (approx. 12-16 h).

Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:

Approx. 24 hours (normal climatic conditions, 20-23°C/50-65% rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

Coverage:

Product coverage for 1 coat is 40-50 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Note:

2K Wood Oil can be used solely with the hardener which was developed for it. Leftover mixed product cannot be used after pot time has expired and must be disposed appropriately. Wood surfaces treated with 2K Wood Oil are easy to maintain. Remove coarse dirt with a broom or a vacuum cleaner. To clean, add Osmo Wash and Care concentrate to mop water and clean the surface with a damp (not wet!) mop. To refresh and clean intensively, use Osmo Liquid Wax Cleaner when necessary. If more sheen is desired, after thoroughly drying apply Osmo Liquid Wax Cleaner thinly and polish when dry.

Caution:

Keep out of reach of children. Warning: Materials impregnated with liquid product, such as cloths, may

self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. Safety data sheet available on request. EU limit value for this product (cat. A/j): 500 g/l VOC. This product contains max. 50 g/l VOC.

Disposal:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

Colour tone:

6100 Clear Matt
6111 White Matt
6112 Silver Grey Matt
6114 Graphite Matt
6118 Light Grey Matt
6116 Cherry Matt
6119 Natural Matt
6138 Garnet Matt
6141 Havanna Matt
6143 Cognac Matt
6164 Tobacco Matt
6190 Black Matt

Size:

0.375 l; 1.0 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any previous product information.

Version 01/26