




INTERIOR-WAX

Hard-wearing finish with a wax-like character for wood for interior use!



7393 White
transparent
Satin



7394 White
opaque Satin



Product description:

Transparent or opaque, satin and hard-wearing wood finish with a wax-like character for indoor areas. Osmo Interior-Wax is stain-resistant, water-repellent and abrasion-resistant and smoothens the surface. The wood grain remains visible. Simple application – no primer or sanding between coats needed – this saves time and money. Suitable for wood; microporous surface will not crack, peel or flake. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

Recommended use:

Osmo Interior-Wax is suitable for the protection and decorative finishing of wood in indoor areas: wall and ceiling panelling, moulding and beams as well as furniture, doors and children's toys. It is also suitable for recoating and repairing wood factory finished with Osmo Interior-Wax White Transparent (7393) or White Opaque (7394) and for recoating old wooden ceiling panelling.

Ingredients:

On the basis of a polymer dispersion, waxes, titanium dioxide (white pigment) additives and preservatives (BIT & CIT/MIT). Solvent: water. Full declaration of ingredients on request.

Technical data:

Specific weight: 1.10-1.25 g/cm³

Viscosity: 1300-1700 mPas viscid

Odour: faint/mild, odourless after drying

Flashpoint: not required

pH value: 8.0-9.0

Storage:

2 years or longer if stored in the originally closed container. Do not expose to frost or temperatures above 30 °C!

Surface preparation:

Wood surface must be clean and dry (max. moisture content 18 %, coating temperature min. +10 °C). Osmo Interior-Wax is ready to use, please do no thin, stir well before use. Clean old microporous stains thoroughly. Old paints, varnishes and lacquers must be completely removed. Always wear a dust mask while sanding. Small cracks, larger dents and small holes in the wood can be filled Osmo Wood Filler. Wood treated with Osmo Interior-Wax generally only needs cleaning and then it can be recoated.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

With either Osmo Flat Brush or Osmo Microfibre Roller apply thinly and evenly along the wood grain and spread well. Allow to dry for approx. 3 - 4 hours. If necessary, do a fine-grained (P 240-360) sanding between coats. After drying apply a second thin coat as before. Due to the quick drying properties, do not make sections too wide. For renovations 1 coat will be sufficient for most cases.

Cleaning of tools:

Immediately after use, with soap and water.



Drying time:

Approx. 3-4 hours (normal climatic conditions, 20-23°C/ 50-65% rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

Coverage:

Product coverage for 1 coat is 16 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Recommendation:

Ready to use - do not thin! Stir well. Apply thinly and evenly to the clean wood surface with Osmo Flat Brush or Microfibre Roller along the wood grain and spread well (approx. 60-65 ml/m²). The coating results vary depending on the wood moisture content (max. 18%) and the condition of the wood, along with other factors. Therefore, a trial application should always be carried out - especially on unknown substrates! Impregnate wood species susceptible to blue stain or wood in wet rooms with Osmo Wood Protector (ecological and free of biocides) (drying time 72 hours), if possible on all sides.

Note:

Osmo Interior-Wax is a stand-alone coating. Please do not thin or mix with other coating systems. Attention: When renovating existing wooden panelling on ceilings, do not allow the coating to penetrate the tongue and groove connections cracking and blocking possible!

Caution:

Keep out of reach of children. Contains benzisothiazolinone (BIT); mixture of: chloromethylisothiazolinone (CIT) and methylisothiazolinone (MIT) (3:1) (preservatives). May

produce an allergic reaction. Safety data sheet available on request. EU limit value for this product (cat. A/d): 130 g/l VOC. This product contains max. 70 g/l VOC.

Always follow the information on the product label.

Disposal:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

Colour tone:

7393 White transparent Satin
7394 White opaque Satin

Size:

0.75 l; 2.5 l; 5.0 l; 10 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any previous product information.

Version 01/26