




PAINT REMOVER GEL

Removes old Decking-Oil and wood stains evenly and efficiently



6611 Clear



Product description:

Ready-to-use, viscous paint remover especially developed for removing old existing oil surface finishes in outdoor areas. Afterwards the surface can be revived/neutralised with Osmo Wood Reviver Power-Gel and then re-oiled.

Recommended use:

Osmo Paint Remover Gel removes old Decking-Oil and wood stains on timber decking and garden furniture made of wood. Ideal for removing oil-based surface finishes on partially weathered timber decking so that an overall oil-free wood surface is achieved.

Ingredients:

Osmo Paint Remover Gel contains non-ionic surfactants (< 5 %), lye. Solvent: water.

Technical data:

Specific weight: 1.05 +/- 0.05 g/cm³

Odour: faint/mild, odourless after drying

pH value: 11.0-11.5

Storage:

2 years or longer if stored in the originally closed container. Do not expose to frost or temperatures above 30 °C!

Surface preparation:

Before the application, remove any debris from the surface with a broom or hand broom. Cover all areas that should not be treated. Osmo Paint Remover Gel is ready to use. Do not thin. Stir well before and

during use as some separation in product may occur after some time. Before treatment with Osmo Paint Remover Gel, test the substrate. A trial application is absolutely necessary! Suitability, reaction time and required application amount can be determined on sample trial area. Caution should be taken when used on veneers! Veneers may loosen from substrate.

Methods of Application:

With a brush or Osmo Decking Cleaning Brush, apply product thick enough (approx. 200 ml/m²) on the dry surface to be cleaned, and allow the gel to react for 60 minutes (but not longer than needed!). Keep surface damp during reaction time (e.g. with a spray bottle). Afterwards scrub the surface with a lot of clear water along the wood grain. After drying, inspect the wood surface and repeat the process if necessary. Residues from Paint Remover Gel may have a negative influence on the drying and adhesive properties of subsequent coatings. Therefore, it is absolutely essential to thoroughly rinse the surface after treatment. If the wood surface should be re-oiled, the surface must be neutralised and revived with Osmo Wood Reviver Power-Gel after drying.

Cleaning of tools:

With soap and water.

Drying time:

Before applying a new coating, allow the wood to dry thoroughly (approx. 24-48 hours). Lower temperatures and/or higher air humidity may increase drying times significantly.



Coverage:

1 litre covers approx. 5 m² with one application.

Note:

Cover all areas that should not be treated, such as sensitive plants, porous substrates (e.g. light-coloured pebble dashed concrete, render etc.), aluminium, zinc or lacquered surfaces. Have mop water ready to rinse any surfaces (e.g. aluminium, zinc or lacquered areas) that have accidentally come into contact with the gel. Please wear safety gloves and goggles. Residues from Paint Remover Gel may have a negative influence on the drying and adhesive properties of subsequent coatings. Therefore, it is absolutely essential to thoroughly rinse the surface after treatment.

Caution:

May be corrosive to metals. Causes skin irritation. Causes serious eye irritation. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep only in original packaging. Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. Reacts with acids with evolution of heat. Risk of splashing! Caution! Do not use with other products. Contains DECYL GLUCOSIDE < 5 %.

Always follow the information on the product label.



Warning

Disposal:

Dispose of product residuals according to the official guidelines (European Waste Code (EWC)-Code 08 01 21*). Only completely emptied cans can be recycled.

Colour tone:

6611 Clear

Size:

0.5 l; 2.5 l; 5.0 l; 10 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any previous product information.

Version 01/26