



COUNTRY COLOUR

Variety of colours and unsurpassed durability – for all weather conditions!



Product description:

Opaque, at first slightly satin-gloss then satin, natural oil based finish for wood in outdoor areas. Wood tone and grain is covered. The wood texture remains noticeable. Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weatherproof and UV stable surface does not crack, peel, flake or blister. No sanding necessary, just simply recoat; no primer is needed. Easy and seamless application. Finish stays workable while coating. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3)

Recommended use:

Osmo Country Colour is best suited for all wood in outdoor areas where an especially durable coating is required: timber cladding, balconies, windows and window shutters, fences, pergolas, wooden shingles, garden furniture and garden sheds, carports etc. Ideal for renewing old microporous finishes and weathered wooden surfaces.

Ingredients:

Based on natural plant oils (sunflower oil, soybean oil and thistle oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying

agents) and water-repellent additives. Dearomatised white spirit (benzene-free). Detailed declaration of ingredients available upon request.

Technical data:

Specific weight: 1.0-1.35 g/cm³
 Viscosity: 20-60s DIN EN ISO 2431/4 mm, viscid
 Odour: faint/mild, odourless after drying
 Flashpoint: > 60°C, acc. DIN EN ISO 2719

Storage:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

Surface preparation:

Wood surface must be clean, dry and frost-free (moisture content max. 20%). Osmo Country Colour is ready to use. Do not thin. Stir well before use. If possible, please apply the first coat to all sides before installation. Clean old microporous stains thoroughly. Old paints, varnishes and lacquers must be completely removed. Always wear dust mask while sanding.

The finished surface and the product coverage are



influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

With Osmo Flat Brush or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and spread well. Allow to dry for approx. 10-12 hours under good ventilation. After drying, apply a second coat – also thinly. When renovating, one coat applied to the clean and dry surface is usually sufficient.

Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:

Approx. 12 hours (normal climatic conditions, 20-23°C / 50-65 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

Coverage:

Product coverage for 1 coat is 26 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Recommendation:

Ready to use – do not thin! Apply to the clean wood thinly with Osmo Flat Brush, Finish Applicator Fleece or Microfibre Roller and spread well along the wood grain. The coating results depend on several factors, including the condition of the wood and the wood moisture content (max. 20%). Therefore, a trial application is always required, especially for unfamiliar surfaces.

If additional protection against blue stain, rot and insect attack is desired, pre-treat the wood – if possible, on all sides – with Osmo WR Base Coat 4001.

Note:

Country Colour, which has been trusted for over decades, is also available in the colour of your choice. Starting from 2.5 litres per colour tone, available in 186 RAL Classic and 1950 NCS colour tones, as well as with biocidal film protection additives. Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

Caution:

Keep out of reach of children. Safety data sheet available on request. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. EU limit value for this product (cat. A/e): 400 g/l VOC. This product contains max. 400 g/l VOC.

Disposal:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

Colour tone:

2101 White Satin
2203 Light Ochre Satin
2204 Ivory Satin
2205 Sunflower Yellow Satin
2308 Nordic Red Satin
2310 Cedar/Redwood Satin
2311 Signal Red Satin
2404 Fir Green Satin
2501 Labrador Blue Satin
2506 Royal Blue Satin
2507 Dove Blue Satin
2606 Medium Brown Satin
2607 Dark Brown Satin
2703 Charcoal Satin
2704 Dusk Grey Satin
2708 Pebble Grey Satin
2716 Anthracite Grey Satin
2735 Light Grey (RAL 7035) Satin
2742 Traffic Grey A (RAL 7042) Satin

Size:

0.75 l; 2.5 l; 5.0 l; 25 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any



previous product information.

Version 01/26