



WR BASE COAT AQUA

Ready to use, liquid wood preservative!



4008 Clear

Product description:

Osmo WR Base CoatAqua is a ready-to-use waterborne wood preservative. For the protection of wood in outdoor areas without direct ground or water contact against vegetable pests such as blue stain and rot. Osmo WR Base CoatAqua has a very low odour during application, and is odourless when dry.

Recommended use:

Wood preservative against wood-rotting and wood-staining fungi on all exterior wood without direct ground and/or surface water contact, e.g. (not under static loads) windows, shutters, pergolas, fences, timber cladding, garden furniture, etc. Do not use indoors, except for external window frames and external doors.

Ingredients:

0.75% 3-iodo-2-propynyl butylcarbamate (IPBC) (7.5 g/kg); 0.24% propiconazole (ISO) (2.4 g/kg)

Technical data:

Specific weight: 1.01 g/cm³

Viscosity: inviscid

Odour: faint/mild, odourless after drying

Flashpoint: Not applicable.

Storage:

2 years or longer if stored in the originally closed container. Do not expose to frost or temperatures above 30 °C!

Surface preparation:

Wood surface must be clean and dry (moisture



content max. 20%). Osmo WR Base CoatAqua is ready-to-use. Please do no thin. Stir well before use.

Methods of Application:

Coat the clean, dry and frost-free wood generously – if possible on all sides. The product should be applied evenly in order to get best results. Processing conditions: above 5°C / relative humidity below 80%.
- industrial use: dipping, flow-coating, spraying
- professional and amateur use: brush, roller, spraying.

Cleaning of tools:

Immediately after use, with soap and water.

Drying time:

Approx. 24 hours (normal climatic conditions, 20-23 °C/50-65% rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

Coverage:

Product coverage for 1 coat is 5-6 m²/1 l. It depends significantly on the condition of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Note:

Osmo WR Base CoatAqua is not a final coat. For untreated wood, a final treatment (e.g. with Osmo wood coatings) is required within three months. Freshly treated timber must be stored after treatment under shelter or on a hard, impermeable surface to prevent direct losses to soil and water. Any losses should be collected for re-use or disposal.



Manufacturer: Troy Chemical Company B.V.,
Poortweg 4C, NL-2612PA Delft

Caution:

Harmful to aquatic life with long lasting effects. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Read carefully and follow all instructions. Avoid release to the environment. Dispose of contents/container in accordance with national regulations.

Disposal:

This material and its container must be disposed of safely as hazardous waste. Any product collected during application that is not re-used must be disposed of safely as hazardous waste. Do NOT empty into drains. European Waste Code (EWC)-Code: 03 02 05*. HSE: UK-2017-1070

Colour tone:
4008 Clear

Size:
0.75 l; 2.5 l; 5.0 l; 25 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any previous product information.

Version 01/26