





LIQUID WAX CLEANER

Cleans and refreshes in one step!



3029 Clear



3087 White



Product description:

Clear or transparent wax-based care product for occasionally refreshing interior wooden flooring treated with Polyx®-Oil, furniture as well as other interior oiled and waxed wood surfaces. Through appropriate care, the surface is provided with the natural, safe hard waxes. The floor stays hard-wearing without forming a film.

Recommended use:

Osmo Liquid Wax Cleaner is best suited for refreshing all surfaces treated with Osmo Polyx®-Oil or lacquered flooring and furniture surfaces. It is also ideal for removing tough stains, e.g. grease, shoe polish and scuff marks from shoe soles.

Ingredients:

Based on natural plant waxes; paraffin, aliphatic hydrocarbons (>30%). Detailed declaration of ingredients available upon request.

Technical data:

Specific weight: 0.77-0.8 g/cm³

Viscosity: >30s DIN EN ISO 2431/3 mm, viscid

Odour: faint/mild, odourless after drying

Flashpoint: > 60°C, acc. DIN EN ISO 2719

Storage:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

Surface preparation:

Wood surface must be dust-free and dry. A dust mop, a mop or a vacuum cleaner is usually suitable for removing dust. For simple cleaning and upkeep,

Osmo Cleaning Kit for Floors (Dust-Mop, Micro-Mop Plush and an Active Fibre Cloth) is highly recommended. High traffic and high wear floor surfaces, for example commercial interiors, should first be cleaned with a damp mop (water with Osmo Wash and Care) and wiped dry.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

Manual application: For removing stains and intensive maintenance, please use Osmo Liquid Wax Cleaner together with Osmo Active Fibre Cloth (approx. 2 teaspoons per m²). Rub away especially tough stains with Osmo Liquid Wax Cleaner with a cloth or a scouring pad. Machine application: Apply Osmo Liquid Wax Cleaner with Osmo FlooreXcenter or a single disc machine and a white pad (approx. 2 teaspoons per m²). Spread Osmo Liquid Wax Cleaner evenly on the surface and buff in. If streaks appear, turn pad over or replace with a new pad. For more information, see FlooreXcenter description. For more sheen, buff the dried surface with a white pad.

Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:

Approx. 30-40 minutes (normal climatic conditions, 20-23°C/50-65 % rel. humidity). Ventilate well while



drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

Coverage:

Product coverage of Osmo Liquid Wax Cleaner strongly depends on the absorption and on the level of contamination on the substrate. (1 litre of care product covers approx. 80-100 m², 2 teaspoons for approx. 1 m²).

Recommendation:

Ready to use - do not thin! Apply thinly and evenly to the clean wood surface with Active Fibre Cloth found in the Osmo Cleaning Kit for Floors (Dust-Mop, Micro-Mop Plush and Active Fibre Cloth) and spread well (approx. 2 teaspoons/m²). The coating results vary depending on the condition of the wood, along with other factors. Therefore, a trial application should always be carried out - especially on unknown substrates! Over the years, it is absolutely essential to re-apply the necessary oil ingredients in Polyx®-Oil to flooring. On especially high traffic areas, recoat the cleaned area with a clear Osmo Polyx®-Oil.

Note:

By applying hard waxes regularly, flooring stays refreshed and stain and wear resistance is improved. However over the years, it is absolutely essential to re-apply the necessary oil ingredients in Polyx®-Oil to flooring. Only use very sparingly otherwise traffic marks may appear. Use Osmo Liquid Wax Cleaner White only on white substrates. On especially high traffic areas, refinish the cleaned area with Osmo Polyx®-Oil.

Caution:

Keep out of reach of children. Repeated exposure

may cause skin dryness or cracking. Safety data sheet available on request. Contains >30% aliphatic hydrocarbons.

Disposal:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

Colour tone:

3029 Clear
3087 White

Size:

0.5 l; 1.0 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. For information specific to a certain country or region, please consult your local wholesaler or dealer. Upon publication of a new version of this product information, the new information shall replace any previous product information.

Version 01/26